

# BZ-211

Fully-automatic Strapping Machine  
(Online)

MODEL SERIES:

EDGE



## Main Features

● Easy operation	● Sensor/Limit Switch/Relay: OMRON
● Easy maintenance	● Quality assurance
● 60 sec. auto-stop: electricity-saving	● Contactor: Schneider/Siemens
● Advanced PLC : LG / SIMENS	● Auto/Manual Operation: OMRON/P&F/GIGO
● Motor : MIEWA/LUSON/GPG	● Power consumption: 2 KW

**BANDMA EQUIP CORP LIMITED**

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041

## Basic Information

Model	BZ-211 (BANDMA EDGE)
<b>Power Supply and Power</b>	415V / 50 Hz, (1.5 kW) 10 A
<b>Bailing Speed</b>	≤ 2.5 sec/path
<b>Strapping Force</b>	0.60 kg
<b>Requirement for bailing strap</b>	Width: 9-15 mm ; Thickness: 0.6-0.8 mm
<b>Strapping Mode</b>	Parallel strapping, 1 several strips, modes photoelectric control, manual operation, etc.
<b>Dimensions</b>	L1580 mm × W650 mm × H1418 mm
<b>Sheet Thickness</b>	2 mm - 4 mm
<b>Frame Size</b>	W1000 mm × H800 mm
<b>Weight</b>	300 kg
<b>Noise</b>	≤ 75 DB
<b>Arch Size</b>	W1000 mm × H800 mm
<b>Environment Condition</b>	Humidity ≤ 98%, Temperature 0-40°C
<b>Bottom Adhesive</b>	Adhesive surface ≥ 90%, Adhesive with ≥ 20%, Deviation of adhesive positions ≤ mm
<b>Remarks</b>	Adhesive position is ≥ 15 mm from the ground

**BANDMA EQUIP CORP LIMITED**

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041