

FPR-400

MODEL SERIES:



Flexible Powered Roller Conveyor



Description:

Flexible Powered Roller Conveyors is an extendable motorized roller conveyor with controllable conveying speed & direction, adjustable supporting leg height and enough power supply by one mini motor per meter. It is well qualified to intensively transport goods especially with flat bottom in the warehouse, storehouse, workshop factory, harbor, dock, etc, which largely satisfies the easy, safe, quick and efficient goods delivery.

MODEL	FPR-400
Close Length (mm)	1840
Open Length (mm)	4800
Width (mm)	800
Adjustable Height (mm)	800-1000
Max. Load (kg/m)	50
Adjustable Speed (m/min)	10-18



Remark:

Belt	High Quality O ring PU belt, L260 × 5 mm
Width	800 mm as standard (700 mm, 600 mm as optional)
Roller	Dia 50*1.5 mm galvanized steel roller, Max. 130 mm center to center
Control Box	Forward / Stop / Reverse
Motor	GPG motor 90 V
Vfd	DELTA
Caster	Dia 125 mm high quality swivel lockable polyurethane casters
Hooks	Convenient to join two or more units quickly and easily
Frame	3.5 mm thickness galvanized curved join plates with better load
Package End Stop Guard	Available
Leg	32 × 32 powder coated tube with 25 × 25 galvanized tube inside
No. of Legs	16
Wheels	360° moving wheels
Application	Perfect to convey cartons and boxes

Note : Handles and Stopper frames of the Conveyors will be provided.

BANDMA EQUIPCORP LIMITED

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041